

Gen^oM Manual

For Gen^oM version 3

Sara Fleury – sara.fleury@laas.fr
Matthieu Herrb – matthieu.herrb@laas.fr
Anthony Mallet – anthony.mallet@laas.fr
Cédric Pasteur

Copyright 2009-2010 ©LAAS/CNRS

March 18, 2011

Contents

1	Introduction	1
2	Component model	3
3	G^{en}oM overview	5
4	A minimal example	7
5	Input file format	9
5.1	Overview	9
5.2	Preprocessing	9
5.3	Dotgen grammar	10
5.4	Dotgen specification	14
5.5	Identifiers and reserved keywords	15
5.6	Line directives	16
5.7	Module declaration	16
5.8	Type declaration	16
5.9	Constant declaration	17
6	G^{en}oM IDL mappings	19
6.1	C mappings	19
6.1.1	Scoped names	19
6.1.2	Mapping for constants	19
6.1.3	Mapping for basic data types	20
6.1.4	Mapping for enumerated types	20
6.1.5	Mapping for strings	20
6.1.6	Mapping for arrays	21
6.1.7	Mapping for structure types	21
6.1.8	Mapping for union types	21
6.1.9	Mapping for sequence types	22
6.2	C++ mappings	22
6.2.1	Scoped names	22
6.2.2	Mapping for constants	23
6.2.3	Mapping for basic data types	23
6.2.4	Mapping for enumerated types	23
6.2.5	Mapping for strings	24
6.2.6	Mapping for arrays	24
6.2.7	Mapping for structure types	24
6.2.8	Mapping for union types	25
6.2.9	Mapping for sequence types	25

7	Running G^{en}oM	27
7.1	Synopsis	27
7.2	Description	27
7.3	General options	28
7.4	Template options	29
7.5	Environment variables	29
8	Templates	31
8.1	The template command	31
8.2	The engine command	33
8.3	The dotgen command	34
8.3.1	dotgen genom	34
8.3.2	dotgen template	35
8.3.3	dotgen input	35
8.3.4	dotgen parse	36
8.3.5	dotgen types	36
8.3.6	dotgen components	37
8.4	The language command	37
8.5	The object command	40
	Bibliography	43
	Index	45

Introduction

Component model

G^{en}oM overview

A minimal example

Input file format

This chapter describes the G^{en}oM Input File Format (dotgen) semantics and gives the syntax for dotgen grammatical constructs.

5.1 Overview

The G^{en}oM Input File Format (dotgen) is the language used to formally describe a G^{en}oM component in terms of services and data types it provides. A description written in dotgen completely defines the interface and the internals of a component.

A description of the dotgen preprocessing is presented in section 5.2, [Preprocessing](#). The grammar is presented in section 5.3, [Dotgen grammar](#), and associated semantics is described in the rest of this chapter either in place or through references to other sub sections of this chapter.

A source file containing a dotgen component specification must have a ".gen" extension. The description of the dotgen grammar uses a syntax notation that is similar to Extended Backus-Naur Format (EBNF). Table 5.1, [dotgen EBNF symbols](#), lists the symbols used in this format and their meaning.

5.2 Preprocessing

A dotgen specification consists of one or more files that are preprocessed. The preprocessing performs file inclusion and macro substitution and is controlled by directives introduced by lines having # as the first character other than white space. The preprocessing is done by the C preprocessor available on the host system and configured during the build of G^{en}oM. It is invoked as a separate process.

Symbol	Meaning
::=	Definition.
	Alternation.
text	Nonterminals.
"text"	Terminals.
(...)	Grouping.
{ ... }	Repetition: may occur zero or any number of times.
[...]	Option: may occur zero or one time.

Table 5.1: dotgen EBNF symbols

Preprocessor directives beginning with # have their own syntax (namely, the C preprocessor syntax), independent of the dotgen language and not described in this document. See for instance [1] for a documentation. Directives may appear anywhere in the source file but are not seen nor interpreted by G^{en}oM. The primary use of the preprocessing facilities is to include definitions (especially type definitions) from other dotgen specifications. Text in files included with a #include directive is treated as if it appeared in the including file.

5.3 Dotgen grammar

(1)	spec	::= { statement } statement
(2)	statement	::= idlstatement genomstatement cpphash
(3)	idlstatement	::= (module const_dcl type_dcl) ";"
(4)	genomstatement	::= (template component ids attribute port task service) ";"
(5)	template	::= TEMPLATE identifier ["{" attr_list }"]
(6)	component	::= "component" identifier ["{" attr_list }"]
(7)	port	::= port_dir port_kind "<" port_type ">" identifier port_array
(8)	port_type	::= [type_spec]
(9)	port_dir	::= "inport" "outport"
(10)	port_array	::= ["[" "]"]
(11)	port_kind	::= "data" "event"
(12)	ids	::= scope_push_ids "{" member_list }"
(13)	attribute	::= "attribute" inited_ids_member_list
(14)	task	::= "task" identifier ["{" attr_list }"]
(15)	service	::= "service" identifier "(" param_list ")" ["{" attr_list }"]
(16)	attr_list	::= { attr ";" } attr ";"
(17)	attr	::= "doc" ":" string_literals "version" ":" string_literals "lang" ":" string_literals "email" ":" string_literals "require" ":" string_list "build-require" ":" string_list "clock-rate" ":" const_expr time_unit "period" ":" const_expr time_unit "delay" ":" const_expr time_unit "priority" ":" positive_int_const "scheduling" ":" "real-time" "stack" ":" positive_int_const size_unit "throw" ":" event_list "task" ":" identifier "interrupts" ":" identifier_list "before" ":" identifier_list "after" ":" identifier_list "validate" ":" validate "codel" codel

(18)	validate	::= identifier "(" param_list ")"
(19)	code1	::= event_list ":" identifier "(" param_list ") "yield" event_list
(20)	event_list	::= identifier_list
(21)	param_list	::= [{ param "," } param]
(22)	param	::= ids_param_dir inited_ids_member port_param_dir inited_port_member
(23)	inited_ids_member_list	::= { inited_ids_member "," } inited_ids_member
(24)	inited_ids_member	::= named_ids_member ["=" initializer]
(25)	named_ids_member	::= ids_member ids_member ":" identifier ":" identifier
(26)	ids_member	::= identifier ids_member param_member
(27)	inited_port_member	::= named_port_member ["=" initializer]
(28)	named_port_member	::= port_member [":" identifier]
(29)	port_member	::= identifier identifier "[" ids_member "]" port_member param_member
(30)	param_member	::= "." identifier "[" positive_int_const "]"
(31)	ids_param_dir	::= "in" "out" "inout"
(32)	port_param_dir	::= "inport" "outport"
(33)	initializer_list	::= [{ initializer "," } initializer]
(34)	initializer	::= initializer_value ":" string_literals initializer_value ":" string_literals
(35)	initializer_value	::= const_expr "{" initializer_list " "[" positive_int_const "]" "=" const_expr "[" positive_int_const "]" "=" "{" initializer_list "." identifier "=" const_expr "." identifier "=" "{" initializer_list "
(36)	module	::= "module" module_name "{ (idlspec " ")"
(37)	module_name	::= identifier
(38)	idldef	::= idlstatement cphash
(39)	idlspec	::= { idldef } idldef
(40)	const_dcl	::= "const" const_type identifier "=" const_expr
(41)	const_type	::= integer_type char_type boolean_type floating_pt_type octet_type string_type named_type

(42)	type_dcl	::= constructed_type "typedef" alias_list forward_dcl
(43)	constructed_type	::= struct_type union_type enum_type
(44)	alias_list	::= (type_spec alias_list ",") declarator
(45)	struct_type	::= "struct" scope_push_struct "{" member_list "}"
(46)	union_type	::= "union" scope_push_union "switch" "(" switch_type_spec ")" "{" switch_body "}"
(47)	enum_type	::= "enum" identifier "{" enumerator_list "}"
(48)	forward_dcl	::= ("struct" "union") identifier
(49)	declarator	::= simple_declarator array_declarator
(50)	simple_declarator	::= identifier
(51)	array_declarator	::= (simple_declarator array_declarator) fixed_array_size
(52)	fixed_array_size	::= "[" positive_int_const "]"
(53)	type_spec	::= simple_type_spec constructed_type_spec
(54)	simple_type_spec	::= base_type_spec template_type_spec named_type
(55)	constructed_type_spec	::= constructed_type
(56)	named_type	::= scoped_name
(57)	base_type_spec	::= boolean_type integer_type floating_pt_type char_type octet_type any_type
(58)	template_type_spec	::= sequence_type string_type fixed_type
(59)	integer_type	::= signed_int unsigned_int
(60)	floating_pt_type	::= float_type double_type
(61)	signed_int	::= signed_longlong_int signed_long_int signed_short_int
(62)	unsigned_int	::= unsigned_longlong_int unsigned_long_int unsigned_short_int
(63)	unsigned_short_int	::= "unsigned" "short"
(64)	unsigned_long_int	::= "unsigned" "long"
(65)	unsigned_longlong_int	::= "unsigned" "long" "long"
(66)	signed_short_int	::= "short"
(67)	signed_long_int	::= "long"

```

(68) signed_longlong_int ::= "long" "long"
(69) float_type          ::= "float"
(70) double_type        ::= "double"
(71) char_type          ::= "char"
(72) boolean_type       ::= "boolean"
(73) octet_type         ::= "octet"
(74) any_type           ::= "any"
(75) string_type        ::= "string" [ "<" positive_int_const ">" ]
(76) sequence_type     ::= "sequence" "<" simple_type_spec ( ","
                        positive_int_const ">" | ">" )
(77) fixed_type         ::= "fixed" [ "<" positive_int_const ","
                        positive_int_const ">" ]
(78) switch_type_spec  ::= integer_type
                        | char_type
                        | boolean_type
                        | enum_type
                        | named_type
(79) switch_body        ::= { case } case
(80) member_list        ::= { member ";" } member ";"
(81) member             ::= ( type_spec | member "," ) declarator
(82) case               ::= case_label_list type_spec declarator ";"
(83) case_label_list   ::= { case_label } case_label
(84) case_label         ::= ( "case" const_expr | "default" ) ":"
(85) enumerator_list   ::= { enumerator "," } enumerator
(86) enumerator         ::= identifier
(87) scope_push_struct ::= identifier
(88) scope_push_union  ::= identifier
(89) scope_push_ids    ::= "ids"
(90) scoped_name       ::= [ [ scoped_name ] ":" ] identifier
(91) const_expr        ::= or_expr
(92) positive_int_const ::= const_expr
(93) or_expr           ::= { xor_expr "|" } xor_expr
(94) xor_expr          ::= { and_expr "^" } and_expr
(95) and_expr          ::= { shift_expr "&" } shift_expr
(96) shift_expr        ::= { add_expr ( ">>" | "<<" ) } add_expr
(97) add_expr          ::= { mult_expr ( "+" | "-" ) } mult_expr
(98) mult_expr         ::= { unary_expr ( "*" | "/" | "%" ) } unary_expr
(99) unary_expr        ::= [ "-" | "+" | "~" ] primary_expr
(100) primary_expr     ::= literal
                        | "(" const_expr ")"
                        | named_type
(101) literal          ::= "TRUE"
                        | "FALSE"
                        | integer_literal
                        | "<float_literal>"
                        | "<fixed_literal>"
                        | "<char_literal>"
                        | string_literals

```

```

(102)  string_literals      ::= { string_literal } string_literal
(103)  string_list         ::= { string_literals "," } string_literals
(104)  time_unit           ::= [ "s" | "ms" | "us" ]
(105)  size_unit           ::= [ "k" | "m" ]
(106)  identifier          ::= "[A-Za-z_][A-Za-z0-9_]*"
      | "s"
      | "ms"
      | "us"
      | "k"
      | "m"
      | "real-time"
      | TEMPLATE
      | "component"
      | "ids"
      | "attribute"
      | "version"
      | "lang"
      | "email"
      | "require"
      | "build-require"
      | "clock-rate"
      | "task"
      | "period"
      | "delay"
      | "priority"
      | "scheduling"
      | "stack"
      | "codel"
      | "validate"
      | "yield"
      | "throw"
      | "doc"
      | "interrupts"
      | "before"
      | "after"
      | "event"
      | "data"
      | "inport"
      | "outport"
      | "in"
      | "out"
      | "inout"
(107)  identifier_list    ::= { identifier "," } identifier
(108)  cpphash            ::= "#" integer_literal string_literal ( "\n" |
      integer_literal "\n" )

```

5.4 Dotgen specification

A dotgen specification consists of one or more statements. Statements are either IDL statements, G^{en}oM statements or cpp line directives. The syntax is:

```

(1)  spec                  ::= { statement } statement
(2)  statement             ::= idlstatement
      | genomstatement
      | cpphash

```

- ```
(3) idlstatement ::= (module | const_dcl | type_dcl) ";"
(4) genomstatement ::= (template | component | ids | attribute | port |
 task | service) ";"
```

Definitions are named by the mean of identifiers: see section 5.5, [Identifiers and reserved keywords](#). Cpp line directives are normally issued by the C preprocessor and are used to define the current input file name and line number (section 5.6, [Line directives](#)).

An IDL statement defines types (see section 5.8, [Type declaration](#)), constants (see section 5.9, [Constant declaration](#)) or IDL modules containing types and constants (see section 5.7, [Module declaration](#)). The syntax follows closely the subset the OMG IDL specification corresponding to type and constants definitions (see Part I, chapter 7 of [2]). Note that this subset of the dogten grammar is not in any manner tied to OMG IDL and may diverge from future OMG specifications.

A GenoM statement defines components, communication ports, services and execution contexts called tasks.

## 5.5 Identifiers and reserved keywords

An identifier is a sequence of ASCII alphabetic, digit, and underscore ("\_") characters. The first character must be an ASCII alphabetic character.

- ```
(106)  identifier      ::= "[A-Za-z_][A-Za-z0-9_]*"
        | "s"
        | "ms"
        | "us"
        | "k"
        | "m"
        | "real-time"
        | TEMPLATE
        | "component"
        | "ids"
        | "attribute"
        | "version"
        | "lang"
        | "email"
        | "require"
        | "build-require"
        | "clock-rate"
        | "task"
        | "period"
        | "delay"
        | "priority"
        | "scheduling"
        | "stack"
        | "codel"
        | "validate"
        | "yield"
        | "throw"
        | "doc"
        | "interrupts"
        | "before"
        | "after"
        | "event"
        | "data"
```

```

| "inport"
| "outport"
| "in"
| "out"
| "inout"

```

Words that are reserved keywords in the dotgen language are valid identifiers where their use is not ambiguous.

5.6 Line directives

Line directives are normally not used. They are inserted by `cpp`, as a result of preprocessing the input file (section 5.2). They can be used mostly to achieve special effects on error reporting or similar.

A line directive starts with the `#` sign:

```
(108)  cpphash          ::= "#" integer_literal string_literal ( "\n" |
                                integer_literal "\n" )
```

The `#` sign is followed by the current line number and file name of the source file, optionally followed by a numeric flag. The flag is never used by G^{en}oM. Its meaning depends on the C preprocessor used: see for instance chapter 1.8, C preprocessor output, of the FSF C preprocessor [1].

The file name and line number replace the current value kept internally by G^{en}oM and are used in error reporting messages as well as a few other places.

5.7 Module declaration

A module definition satisfies the following syntax:

```
(36)  module           ::= "module" module_name "{" ( idlspec "}" | "}" )
(37)  module_name     ::= identifier
(38)  idldef          ::= idlstatement
                                | cpphash
(39)  idlspec         ::= { idldef } idldef
```

The only effect of a module is to scope IDL identifiers. It is similar to a C++ or Java namespace; it is considered good practice to enclose your type definitions inside a module definition to prevent name clashes between components.

5.8 Type declaration

Type declarations define new data types and associate a name (an identifier) with it. The `typedef` keyword can be used to name an existing type. The constructed types `struct`, `union` and `enum` also name the type they define. The syntax is the following:

```
(42)  type_dcl        ::= constructed_type
                                | "typedef" alias_list
                                | forward_dcl
(43)  constructed_type ::= struct_type
                                | union_type
                                | enum_type
(44)  alias_list      ::= ( type_spec | alias_list "," ) declarator
```

A type specification is the description of a type. It can be used in a `typedef` construct or anywhere a typed value is expected.

- ```
(53) type_spec ::= simple_type_spec
 | constructed_type_spec

(54) simple_type_spec ::= base_type_spec
 | template_type_spec
 | named_type

(57) base_type_spec ::= boolean_type
 | integer_type
 | floating_pt_type
 | char_type
 | octet_type
 | any_type

(58) template_type_spec ::= sequence_type
 | string_type
 | fixed_type

(55) constructed_type_spec ::= constructed_type

(56) named_type ::= scoped_name

(90) scoped_name ::= [[scoped_name] "::"] identifier

(49) declarator ::= simple_declarator
 | array_declarator

(50) simple_declarator ::= identifier
```

## 5.9 Constant declaration

- ```
(40)  const_dcl         ::= "const" const_type identifier "=" const_expr
```


GenoM IDL mappings

GenoM IDL is independent of the programming language used to implement the services and internals of a component. In order to use the GenoM generated source code, it is necessary for programmers to know how to access the service parameters and ports from their programming languages. This chapter defines the mapping of GenoM IDL constructs to the supported programming languages.

The mapping between GenoM IDL and a programming language diverges from the OMG CORBA standard. This is unfortunate, because this might lead to some confusion for the developers used to OMG CORBA, but it was necessary to define mappings well targetting real-time platforms. The design strategy that guided the definition of those mappings was to try to have contiguous memory segments, that do not require memory management primitives, for most of the data types. Only unbounded string and sequences do not follow this scheme.

GenoM currently implements mappings for the C and C++ languages. For the C language, see section 6.1, [C mappings](#). For the C++ language, see section 6.2, [C++ mappings](#),

6.1 C mappings

6.1.1 Scoped names

The C mappings always use the global name for a type or a constant. The C global name corresponding to a GenoM IDL global name is derived by converting occurrences of ":" to "_" (an underscore) and eliminating the leading underscore.

6.1.2 Mapping for constants

In C, constants defined in dotgen are `#defined`. For instance, the following IDL:

```
const long longint = 1;
const string str = "string example";
```

would map into

```
#define longint 1
#define str "string example"
```

The identifier can be referenced at any point in the user's code where a literal of that type is legal.

IDL	C
boolean	bool
unsigned short	uint16_t
short	int16_t
unsigned long	uint32_t
long	int32_t
unsigned long long	uint64_t
long long	int64_t
float	float
double	double
char	char
octet	uint8_t
any	type any not implemented yet

Table 6.1: Basic data types C mappings

6.1.3 Mapping for basic data types

The basic data types have the mappings shown in Table 6.1, [Basic data types C mappings](#). Integer types use the C99 fixed size integer types as provided by the `stdint.h` standard header. Users do not have to include this header: the template mapping generation procedure output the appropriate `#include` directive along with the mappings for the integer types.

6.1.4 Mapping for enumerated types

The C mapping of an IDL `enum` type is an unsigned, 32 bits wide integer. Each enumerator in an `enum` is `#defined` with an appropriate unsigned integer value conforming to the ordering constraints.

For instance, the following IDL:

```
enum e {
    value1,
    value2
};
```

would map, according to the scoped names rules, into

```
typedef uint32_t e
#define e_value1 1
#define e_value2 2
```

6.1.5 Mapping for strings

G^{en}oM IDL bounded strings are mapped to nul terminated character arrays (i.e., C strings). Unbounded strings are mapped to a pointer on such a character array.

For instance, the following *OMG* IDL declarations:

```
typedef string unbounded;
typedef string<16> bounded;
```

would map into

```
typedef char *unbounded;
typedef char bounded[16];
```

6.1.6 Mapping for arrays

GenoM IDL arrays map directly to C arrays. All array indices run from 0 to `size-1`.

For instance, the following IDL:

```
typedef long array[4][16];
```

would map into

```
typedef int32_t array[4][16];
```

6.1.7 Mapping for structure types

GenoM IDL structures map directly onto C `structs`. Note that these structures may potentially include padding.

For instance, the following IDL:

```
struct s {
    long a;
    long b;
};
```

would map into

```
typedef struct {
    int32_t a;
    int32_t b;
} s;
```

6.1.8 Mapping for union types

GenoM IDL unions map onto C `structs`. The discriminator in the enum is referred to as `_d`, the union itself is referred to as `_u`.

For instance, the following IDL:

```
union u switch(long) {
    case 1: long a;
    case 2: float b;
    default: char c;
};
```

would map into

```
typedef struct {
    int32_t _d;
    union {
        int32_t a;
```

```

        float b;
        char c;
    } _u;
} u;

```

6.1.9 Mapping for sequence types

$G^{en}oM$ IDL sequences mapping differ slightly for bounded or unbounded variations of the sequence. Both types maps onto a C `struct`, with a `_maximum`, `_length` and `_buffer` members.

For unbounded sequences, `buffer` points to a buffer of at most `_maximum` elements and containing `_length` valid elements. An additional member `_release` is a function pointer that can be used to release the storage associated to the `_buffer` and reallocate it. It is the responsibility of the user to maintain the consistency between those members.

For bounded sequences, `buffer` is an array of at most `_maximum` elements and containing `_length` valid elements. Since `_buffer` is an array, no memory management is necessary for this data type.

For instance, the following IDL:

```

typedef sequence<long> unbounded;
typedef sequence<long,16> bounded;

```

would map into

```

typedef struct {
    uint32_t _maximum, _length;
    int32_t *_buffer;
    void (*release)(void *_buffer);
} unbounded;

typedef struct {
    const uint32_t _maximum;
    uint32_t _length;
    int32_t _buffer[16];
} bounded;

```

6.2 C++ mappings

6.2.1 Scoped names

The C++ mappings for scoped names use C++ scopes. IDL `modules` are mapped to `namespaces`. For instance, the following IDL:

```

module m {
    const string str = "scoped string";
};

```

would map into

```

namespace m {
    const std::string str = "scoped string";
}

```

IDL	C++
boolean	bool
unsigned short	uint16_t
short	int16_t
unsigned long	uint32_t
long	int32_t
unsigned long long	uint64_t
long long	int64_t
float	float
double	double
char	char
octet	uint8_t
any	type any not implemented yet

Table 6.2: Basic data types C++ mappings

6.2.2 Mapping for constants

G^{en}oM IDL constants are mapped to a C++ constant. For instance, the following IDL:

```
const long longint = 1;
const string str = "string example";
```

would map into

```
const int32_t longint = 1;
const std::string str = "string example";
```

6.2.3 Mapping for basic data types

The basic data types have the mappings shown in Table 6.2, [Basic data types C++ mappings](#). Integer types use the C99 fixed size integer types as provided by the `stdint.h` standard header (since the C++ `cstdint` header is not part of the C++ at the time of writing this document). Users do not have to include this header: the template mapping generation procedure output the appropriate `#include` directive along with the mappings for the integer types.

6.2.4 Mapping for enumerated types

The C++ mapping of an IDL `enum` type is the corresponding C++ `enum`. An additional constant is generated to guarantee that the type occupies a 32 bits wide integer.

For instance, the following IDL:

```
enum e {
    value1,
    value2
};
```

would map, according to the scoped names rules, into

```
enum e {
    value 1,
    value 2,
    _unused = 0xffffffff,
};
```

6.2.5 Mapping for strings

G^{en}oM IDL bounded strings are mapped to nul terminated character arrays (i.e., C strings) wrapped inside the specific `genom::bounded_string` class. Unbounded strings are mapped to `std::string` provided by the C++ standard.

For instance, the following *OMG IDL* declarations:

```
typedef string unbounded;
typedef string<16> bounded;
```

would map into

```
typedef std::string unbounded;
typedef genom::bounded_string<16> bounded;
```

The `genom::bounded_string` provides the following interface:

```
namespace genom3 {
    template<std::size_t L> struct bounded_string {
        char c[L];
    };
}
```

This minimalistic definition will be refined before the official 3.0 *G^{en}oM* release.

6.2.6 Mapping for arrays

G^{en}oM IDL arrays map directly to C++ arrays. All array indices run from 0 to `size-1`.

For instance, the following *IDL*:

```
typedef long array[4][16];
```

would map into

```
typedef int32_t array[4][16];
```

6.2.7 Mapping for structure types

G^{en}oM IDL structures map directly onto C++ `structs`. Note that these structures may potentially include padding.

For instance, the following *IDL*:

```
struct s {
    long a;
    long b;
};
```

would map into

```
struct s {
    int32_t a;
    int32_t b;
};
```

6.2.8 Mapping for union types

G^{en}oM IDL unions map onto C **structs**. The discriminator in the enum is referred to as `_d`, the union itself is referred to as `_u`.

For instance, the following IDL:

```
union u switch(long) {
    case 1: long a;
    case 2: float b;
    default: char c;
};|
```

would map into

```
struct u {
    int32_t _d;
    union {
        int32_t a;
        float b;
        char c;
    } _u;
};
```

Note that the C++ standard does not allow union members that have a non-trivial constructor. Consequently, the C++ mapping for such kind of unions is not allowed in G^{en}oM either. This concerns **sequences** and **strings**, and structures or unions that contain such a type. You should thus avoid to define such datatypes in G^{en}oM IDL in order to maximize the portability of your definitions.

6.2.9 Mapping for sequence types

G^{en}oM IDL sequences mapping differ for bounded or unbounded variations of the sequence. The unbounded sequence maps onto a C++ `std::vector` provided by the C++ standard. The bounded sequences maps onto the specific `genom3::bounded_vector` class.

For instance, the following IDL:

```
typedef sequence<long> unbounded;
typedef sequence<long,16> bounded;
```

would map into

```
typedef std::vector<int32_t> unbounded;
typedef genom3::bounded_vector<int32_t, 16> bounded;
```

The `genom::bounded_vector` provides the following interface:

```
namespace genom3 {  
    template<typename T, std::size_t L> struct bounded_vector {  
        T e[L];  
    };  
}
```

This minimalistic definition will be refined before the official 3.0 $G^{\text{en}}\text{oM}$ release.

Running G^{en}oM

7.1 Synopsis

```
genom3 [-l] [-h] [--version]
genom3 [-I dir] [-D macro[=value]] [-E|-n] [-v] [-d] file.gen
genom3 [general options] template [template options] file.gen
```

7.2 Description

The G^{en}oM program is a *source code generator* that is used to generate software components from a formal description file.

The input *file* is expected to contain the description of the services, input and output ports, data types definitions and execution contexts of a software component, written in the *dotgen* language.

The dotgen specification is first processed by a C preprocessor before it is parsed by G^{en}oM and transformed into an abstract syntax tree. The program used as a C preprocessor can be changed with the `CPP` environment variable. G^{en}oM accepts `-I` and `-D` options that are passed unchanged to the cpp program.

The abstract syntax tree is exported in a format suitable to a *generator engine* that is in charge of a *template* execution for actual source code generation. The generator engine provides a scripting language and a set of procedures for use by templates. The directory where source code for the generator engine is searched can be changed with the `-s` option.

Templates are a set of source files that serve as the basis for source code generation. Templates source files are interpreted by the generator engine. They can contain code written in the scripting language provided by the generator engine, that computes generated output, or regular source code that is appended directly to the generated code. Intermediate files and scripts are saved in a temporary directory before they are copied to the final destination directory. The `-T` option changes the path of the temporary directory. The `-d` option will keep all temporary files instead of deleting them once the program terminates. This is useful only for template development and debugging.

The choice of a template depends on the kind of source code that is wanted by the user. Refer to the documentation of the templates for a description on what they do. The names of the available templates can be listed with the `-l` option. The directory in which templates are looked for can be changed with the `-t` option.

The G^{en}oM program accepts *general options* that affect the general program behaviour. G^{en}oM can also pass *template options* to the template. These options will only affect the template behaviour.

7.3 General options

-I *dir*

Add the directory *dir* to the list of directories to be searched for included files. The *dir* argument is passed as-is to the `cpp` program via the same `-I` option.

When `-r` option is in effect (either explicitly passed on the command line, or configured by default during the build process), an implicit `-I` directive pointing to the directory of the input file is appended to the end of the list of searched directories.

-D *macro*[=*value*]

Predefine *macro*, with definition `1` or *value* if given, in the same way as a `#define` directive would do it. This option is passed as-is to the `cpp` program.

If you are invoking `genom` from the shell, you may have to use the shell quoting character to protect shell's special characters such as spaces.

An implicit macro `__GENOM__` is always defined and contains the version of the `genom` program. This can be used to divert some lines in source files meant to be included by other tools that `genom`, and that contain syntax that `genom` does not understand.

-E

Stop after the preprocessing stage, and do not run `genom` proper. The output of `cpp` is sent to the standard output. `genom` exits with a non-zero status if there are any preprocessing errors, such as a non-existent included file.

-n, --parse-only

Stop after the input file parsing stage, and do not invoke any template. This is useful to check the syntax of the input file. Any errors or warning are reported and `genom` exits with a non-zero status if there are errors.

-l, --list

Print to the standard output the list of available templates. Each line of output contains the name of a template and the `genom` engine that it uses (currently, only Tcl-based templates are supported).

By default, the standard templates directory is searched, but any `-t` option will be taken into account.

-t *path*, --tmpldir=*path*

Use *path* as the directory containing templates. This can be a colon separated list of directories which are searched in order.

This option is useful only for templates not installed in the `genom` standard directories, i.e. `share/genom/<version>/templates` or `share/genom/site-templates`.

path is searched for files matching `dir/*/template.tcl`, where `*` is the actual template name.

-s *dir*, --sysdir=*dir*

Use *dir* as the directory holding `genom` engine files. This option is useful if non-standard engines are to be used. The default value is `share/genom/<version>/engines`.

dir should contain directories named after the engine name.

-T *dir*, --tmpdir=*dir*

Use *dir* as the temporary directory holding intermediate files. See also the environment variable TMPDIR.

-r, --rename

Some `cpp` programs cannot handle correctly files with a `.gen` extension. This option will make `genom` call `cpp` with an input file ending in `.c`, linked to the real input file.

--no-rename

This option is the opposite of `-r`: it forces `genom` to invoke `cpp` directly with the `.gen` input file. This is the default behaviour. If you are using GNU `cpp`, it might be necessary to pass it the additional `-xc` option, to force it to handle the file as C source.

-v, --verbose

Force `genom` to be more verbose while processing input files.

-d, --debug

Activate some debugging options. In particular, temporary files are not deleted. Useful for debugging `genom` itself or generator engines.

--version

Display the version number of the invoked `GenoM`.

-h, --help

Print usage summary and exit.

7.4 Template options

-h, --help

Templates might define their own specific options. The `-h` option is always defined, and prints a summary of supported options. See the template manual for a detailed description. Template options should be passed after the template name, and before the input file name.

7.5 Environment variables

CPP

Define the C preprocessor program to use. The default depends on the value configured during the `genom` build process, but it is most often `gcc -E -xc` on Linux systems.

The CPP program must recognize `-I` and `-D` arguments.

GENOM_TMPL_PATH

The value of `GENOM_TEMPLATE_PATH` is a colon-separated list of directories, much like `PATH`, where `GenoM` looks for templates. Setting this variable overrides the default search path, but any `-t` option takes precedence over this variable.

TMPDIR

Path to the directory holding temporary files. Defaults to `/tmp`.

Templates

8.1 The template command

```
template require file
```

Source tcl *file* and make its content available to the template files. The file name can be absolute or relative. If it is relative, it is interpreted as relative to the template directory (see `dotgen template dir`).

Parameters:

file Tcl input file to source. Any procedure that it creates is made available to the template files.

```
template parse [args list] [file/string/raw file ...]
```

This is the main template function that parses a template source file and instantiate it, writing the result into the current template directory (or in a global variable). This procedure should be invoked for each source file that form a template.

When invoking `template parse`, the last two arguments are the destination file or string. A destination file is specified as `file file` (the filename is relative to the current template output directory). Alternatively, a destination string is specified as `string var`, where *var* is the name of a *global* variable in which the template engine will store the result of the source instantiation.

The output destination file or string is generated by the template from one or several input source. An input source is typically a source file, but it can also be a string or a raw (unprocessed) text. An input source file is specified with `file file`, where *file* is a file name relative to the template directory. An input source read from a string is specified as `string text`, where *text* is any string, processed by the template engine as usual. Finally, a raw, unprocessed source that is copied verbatim to the destination, is specified as `raw text`, where *text* is any string.

Additionally, each input source, defined as above, can be passed a list of optional arguments by using the special `args list` construction as the first argument of the `template parse` command. The list given after `args` can be retrieved from the template source file from the usual `argv` variable.

Examples:

```
template parse file mysrc file mydst
```

Will parse the input file `mysrc`, process it and save the result in `mydst`.

```
template parse args {one two} file mysrc file mydst
```

Will do the same as above, but the template code in the input file `mysrc` will have the list `{one two}` accessible via the `argv` variable.

```
template parse string "test" file mydst
```

Will process the string "test" and save the result in `mydst`.

Parameters:

args This optional argument should be followed by a list of arguments to pass to the template source file. It should be the very first argument, otherwise it is ignored. Each element of the list is available from the template source file in the `argv` array.

perm This optional argument may be set to specify the permissions to be set for the created file.

```
template link src dst
```

Link source file *src* to destination file *dst*. If relative, the source file *src* is interpreted as relative to the template directory and *dst* is interpreted as relative to the current output directory. Absolute file name can be given to override this behaviour.

```
template options { pattern body ... }
```

Define the list of supported options for the template. Argument is a Tcl switch-like script that must define all supported options. It consists of pairs of *pattern body*. If an option matching the *pattern* is passed to the template, the *body* script is evaluated. A special body specified as "-" means that the body for the next pattern will be used for this pattern.

Examples:

```
template options {
-h - -help { puts "help option" }
}
```

This will make the template print the text "help option" whenever -h or -help option is passed to the template.

```
template arg
```

Return the next argument passed to the template, or raise an error if no argument remains.

```
template usage [string]
```

With a *string* argument, this procedure defines the template "usage" message. Unless the template redefines a `-h` option with `template options`, the default behaviour of the template is to print the content of the `template usage` string when `-h` or `-help` option is passed to the template.

`template usage`, when invoked without argument, returns the last usage message defined.

```
template message [string]
```

Print *string* so that it is visible to the end-user. The text is sent on the standard error channel unconditionally.

```
template fatal [string]
```

Print an error message and stop. In verbose mode, print the source location as reported by [info frame].

8.2 The engine command

```
engine mode [ [+-]modespec ... ]
```

Set miscellaneous engine operating mode. The command can be invoked without argument to retrieve the current settings for all supported modes. The command can also be invoked with one or more mode specification to set these modes (see *modespec* argument below).

The list of supported modes is the following:

- **verbose**: turns on or off the verbosity of the engine.
- **overwrite**: when turned on, newly generated files will overwrite existing files without warning. When turned off, the engine will stop with an error if a newly generated file would overwrite an existing file. **overwrite** is by default off.
- **move-if-change**: when turned on, an existing file with the same content as a newly generated file will not be modified (preserving the last modification timestamp). When off, files are systematically updated. **move-if-change** is on by default.
- **debug**: when on, this mode preserves temporary files and tcl programs generated in the temporary directory. Useful only for debugging the template.

Example:

```
engine mode -overwrite +move-if-change
```

Parameters:

modespec A mode specification string. Supported modes are **verbose**, **overwrite**, **move-if-change** and **debug**. If *mode* string is prefixed with a dash (-), it is turned off. If mode is prefixed with a plus (+) or nothing, it is turned on.

Returns:

When called without arguments, the command returns the current configuration of all engine modes.

```
engine chdir dir
```

Change the engine output directory. By default, files are generated in the current directory. This command can be used to generate output in any other directory.

Parameters:

dir The new output directory, absolute or relative to the current working directory.

```
engine pwd
```

Return the current engine output directory.

8.3 The dotgen command

8.3.1 dotgen genom

Those commands implement access to genom program parameters or general information.

```
dotgen genom program
```

Returns the absolute path to the GenoM executable currently running.

```
dotgen genom cmdline
```

Returns a string containing the options passed to the GenoM program.

```
dotgen genom version
```

Returns the full version string of the GenoM program.

```
dotgen genom debug
```

Returns a boolean indicating whether genom was invoked in debugging mode or not.

```
dotgen genom stdout [on]
```

With optional boolean argument *on*, turns on or off the standard output channel of the template engine.

Without argument, the procedure returns the current activation status of the standard output channel.

Parameters:

[on] Turn on/off standard output channel.

Returns:

When called without argument, returns a boolean indicating the current status (on/off) of the standard output channel.

8.3.2 dotgen template

Those commands return information about the template currently being parsed.

```
dotgen template name
```

Return the current template name.

```
dotgen template dir
```

Return a path to the current template directory (the directory holding the template.tcl file).

```
dotgen template sysdir
```

Return a path to the genom system directory.

```
dotgen template tmpdir
```

Return a path to the temporary directory where the template engine writes its temporary files.

8.3.3 dotgen input

Those commands return information about the current genom input file (.gen file).

```
dotgen input file
```

Return the full path to the current .gen file.

```
dotgen input base
```

Return the base name of the current .gen file, i.e. the file name with all directories stripped out.

```
dotgen input dir
```

Return the directory name of the current .gen file.

```
dotgen input notice
```

Return the copyright notice (as text) found in the .gen file. This notice can actually be any text and is the content of the special comment starting with the three characters `'/' '*' '/'`, near the beginning of the .gen file.

8.3.4 dotgen parse

```
dotgen parse file|string data
```

Parse .gen data either from a file or from a string. When parsing is successful, the corresponding objects are exported to the engine.

Parameters:

<i>file/string</i>	Specify if parsing from a file or from a string.
<i>data</i>	When parsing from a file, data is the file name. When parsing from a string, data is the data to be parsed.

8.3.5 dotgen types

This command return information about the type definitions in the .gen file.

```
dotgen types [pattern]
```

This command returns the list of type objects that are defined in the current .gen file. This list may be filtered with the optional *pattern* argument. Each element of the returned list is a type command that can be used to access detailed information about that particular type object.

Parameters:

<i>[pattern]</i>	Filter on the type names. The filter may contain a glob-like pattern (with * or ? wildcards). Only the types whose name match the pattern will be returned.
------------------	---

Returns:

A list of type objects.

8.3.6 dotgen components

This command return information about the components definitions in the .gen file.

```
dotgen components [pattern]
```

This command returns the list of components that are defined in the current .gen file (normally just one). This list may be filtered with the optional *pattern* argument. Each element of the returned list is a component command that can be used to access detailed information about each particular component object.

Parameters:

[pattern] Filter on the component name. The filter may contain a glob-like pattern (with * or ? wildcards). Only the components whose name match the pattern will be returned.

Returns:

A list of component objects.

8.4 The language command

```
language fileext lang [kind]
```

Return the canonical file extension for the given language.

Parameters:

lang The language name. Must be `c` or `c++`.
kind Must be one of the strings `source` or `header`.

```
language comment lang text
```

Return a string that is a valid comment in the given language.

Parameters:

lang The language name. Must be `c`, `c++` or `shell`.
text The string to be commented.

```
language mapping lang [pattern]
```

Generate and return the mapping of the types matching the glob *pattern* (or all types if no pattern is given), for the given language. The returned string is a valid source code for the language.

Parameters:

lang The language name. Must be `c` or `c++`.

pattern A glob pattern to generate the mapping only for those type names that match the pattern.

```
language declarator lang type [var]
```

Return the abstract declarator for *type* or for a variable *var* of that type, in the given language.

Parameters:

lang The language name. Must be `c` or `c++`.
type A type object.
var A string representing the name of a variable of type *type*.

```
language address lang type [var]
```

Return an expression evaluating to the address of a variable.

Parameters:

lang The language name. Must be `c` or `c++`.
type A type object.
var A string representing the name of a variable of type *type*.

```
language dereference lang type [var]
```

Return an expression able to dereference a pointer on a variable.

Parameters:

lang The language name. Must be `c` or `c++`.
type A type object.
var A string representing the name of a variable of type *type*.

```
language parameter lang kind type [var]
```

Return an expression that declares a parameter *var* of type *type*, passed by value or reference according to *kind*.

Parameters:

lang The language name. Must be `c` or `c++`.
kind Must be "value" or "reference".
type A type object.
var A string representing the name of a variable of type *type*.

```
language argument lang kind type [var]
```

Return an expression that passes *var* of type *type* as a parameter, by value or reference according to *kind*.

Parameters:

<i>lang</i>	The language name. Must be <code>c</code> or <code>c++</code> .
<i>kind</i>	Must be "value" or "reference".
<i>type</i>	A type object.
<i>var</i>	A string representing the name of a variable of type <i>type</i> .

```
language member lang type members
```

Return the language construction to access a member of a *type*. If *members* is a list, it is interpreted as a hierarchy. Each element of *members* is interpreted as follow: if it starts with a letter, *type* should be an aggregate type (like `struct`); if it starts with a numeric digit, *type* should be an array type (like `sequence`).

This procedure can typically be used with parameters objects, for which the 'member' subcommand returns a compatible *members* list.

Parameters:

<i>lang</i>	The language name. Must be <code>c</code> or <code>c++</code> .
<i>type</i>	A type object
<i>members</i>	A member name, or a list of hierarchical members to access.

```
language cname lang {string|object}
```

Return the canonical name of the *string* or the G^{en}oM *object*, according to the language *lang*.

If a regular string is given, this procedure typically maps IDL :: scope separator into the native symbol in the given language. If a codel object is given, this procedure returns the symbol name of the codel in the given language.

Parameters:

<i>lang</i>	The language name. Must be <code>c</code> or <code>c++</code> .
<i>string</i>	The name to convert.
<i>object</i>	A G ^{en} oM object. Only class <code>codel</code> is supported at the moment.

```
language signature lang codel [separator [location]]
```

Return the signature of a codel in the given language. If *separator* is given, it is a string that is inserted between the return type of the codel and the codel name (for instance, a `\n` in `C` so that the symbol name is guaranteed to be on the first column).

Parameters:

<i>lang</i>	The language name. Must be <code>c</code> or <code>c++</code> .
<i>codel</i>	A codel object.
<i>separator</i>	A string, inserted between the return type and the codel symbol name.
<i>location</i>	A boolean indicating whether to generate <code>#line</code> directive corresponding to the codel definition in <code>.gen</code> file.

```
language arguments lang codel base
```

Return a list of strings corresponding to each parameter of a codel fetch from the given *base*.

Parameters:

<i>lang</i>	The language name. Must be <code>c</code> or <code>c++</code> .
<i>codel</i>	A codel object.
<i>base</i>	A string from which parameters are fetched.

```
language invoke lang codel params
```

Return a string corresponding to the invocation of a codel in the given language.

Parameters:

<i>lang</i>	The language name. Must be <code>c</code> or <code>c++</code> .
<i>codel</i>	A codel object.
<i>params</i>	The list of parameters passed to the codel. Each element of this list must be a valid string in the <i>lang</i> language corresponding to each parameter value or reference to be passed to the codel.

```
language hfill text [filler] [column]
```

Return a string of length *column* (by default 80), starting with *text* and filled with the *filler* character (by default `-`).

Parameters:

<i>text</i>	The text to fill.
<i>filler</i>	The filler character (by default <code>-</code>).
<i>column</i>	The desired length of the returned string.

8.5 The object command

```
object foreach varlist object body
```

Evaluate *body* for each element of the G^{en}oM *object*, with *varlist* set to the current element. The result of the command is an empty string.

varlist is a list of two or three variable names. The first variable is set to the current element kind, the second variable is set to the current element itself and the third variable (if present) is set to a list of elements representing the hierarchy of objects leading to the current element. If *object* is of class 'type' (a type object), the exploration of the type tree is done in depth-first order. If *body* returns with no error, the next element is explored. If *body* returns with 'continue', the exploration of the current branch is stopped and the next sibling element is explored. If *body* returns with 'break', the procedure returns immediately.

Note: when exploring 'type' objects, an endless recursion is possible if the type in question has a recursive definition (e.g. a structure contains a sequence of the same structure). This potentially endless recursion is allowed on purpose, but it is important that you handle this situation in the *body* script. A potentially endless recursion can be detected if your *body* script encounters either a **forward struct** or a **forward union**. It is up to the caller to determine what to do in this case, but this typically involves returning 'continue' at some point to skip further exploration of that branch.

Parameters:

<i>varlist</i>	varlist A list of variable names of 2 or 3 elements. First variable is set to the current element kind, second variable is set to the current element of object while iterating and optional third element is set to the current element and the hierarchy of elements leading to the current element.
<i>object</i>	object A genom object. Must be of class type .
<i>body</i>	A script evaluated for each element of object.

Bibliography

- [1] Free Software Foundation. The C preprocessor. <http://gcc.gnu.org/onlinedocs/cpp/>.
- [2] Object Management Group. CORBA specification, version 3.1. Part I: CORBA interfaces. <http://www.omg.org/spec/CORBA/3.1/Interfaces/PDF>.

Index

D

dotgen 9
 grammar 10
 identifier 15
 specification 14
dotgen (template command) 34–37
 components 37
 genom 34, 35
 cmdline 34
 debug 34
 program 34
 stdout 35
 version 34
input 35, 36
 base 36
 dir 36
 file 35
 notice 36
parse 36
template 35
 dir 35
 name 35
 sysdir 35
 tmpdir 35
types 36

E

engine (template command) 33, 34
 chdir 34
 mode 33
 pwd 34

I

identifier 15
input
 file format 9
 preprocessing 9

L

language (template command) 37–40
 address 38
 argument 39
 arguments 40
 cname 39
 comment 37
 declarator 38
 dereference 38

fileext 37
hfill 40
invoke 40
mapping 37
member 39
parameter 38
signature 39

O

object (template command) 41
 foreach 41

P

preprocessing 9

T

template (template command) 31–33
 arg 32
 fatal 33
 link 32
 message 33
 options 32
 parse 31
 require 31
 usage 33
template command
 dotgen 34–37
 engine 33, 34
 language 37–40
 object 41
 template 31–33