

# G<sup>en</sup>oM Manual

---

For G<sup>en</sup>oM version 3

Sara Fleury – [sara.fleury@laas.fr](mailto:sara.fleury@laas.fr)  
Matthieu Herrb – [matthieu.herrb@laas.fr](mailto:matthieu.herrb@laas.fr)  
Anthony Mallet – [anthony.mallet@laas.fr](mailto:anthony.mallet@laas.fr)  
Cédric Pasteur

Copyright 2009-2010 ©LAAS/CNRS

November 18, 2011



# Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Component model</b>	<b>3</b>
<b>3</b>	<b>G<sup>en</sup>oM overview</b>	<b>5</b>
<b>4</b>	<b>A minimal example</b>	<b>7</b>
<b>5</b>	<b>Input file format</b>	<b>9</b>
5.1	Overview . . . . .	9
5.2	Preprocessing . . . . .	9
5.3	Dotgen grammar . . . . .	10
5.4	Dotgen specification . . . . .	14
5.5	Identifiers and reserved keywords . . . . .	15
5.6	Line directives . . . . .	16
5.7	Module declaration . . . . .	16
5.8	Type declaration . . . . .	16
5.9	Constant declaration . . . . .	17
<b>6</b>	<b>G<sup>en</sup>oM IDL mappings</b>	<b>19</b>
6.1	C mappings . . . . .	19
6.1.1	Scoped names . . . . .	19
6.1.2	Mapping for constants . . . . .	19
6.1.3	Mapping for basic data types . . . . .	20
6.1.4	Mapping for enumerated types . . . . .	20
6.1.5	Mapping for strings . . . . .	20
6.1.6	Mapping for arrays . . . . .	21
6.1.7	Mapping for structure types . . . . .	21
6.1.8	Mapping for union types . . . . .	21
6.1.9	Mapping for sequence types . . . . .	22
6.2	C++ mappings . . . . .	22
6.2.1	Scoped names . . . . .	22
6.2.2	Mapping for constants . . . . .	23
6.2.3	Mapping for basic data types . . . . .	23
6.2.4	Mapping for enumerated types . . . . .	23
6.2.5	Mapping for strings . . . . .	24
6.2.6	Mapping for arrays . . . . .	24
6.2.7	Mapping for structure types . . . . .	24
6.2.8	Mapping for union types . . . . .	25
6.2.9	Mapping for sequence types . . . . .	25

<b>7</b>	<b>Running G<sup>en</sup>oM</b>	<b>27</b>
7.1	Synopsis . . . . .	27
7.2	Description . . . . .	27
7.3	General options . . . . .	28
7.4	Template options . . . . .	29
7.5	Environment variables . . . . .	29
<b>8</b>	<b>Templates</b>	<b>31</b>
8.1	The template command . . . . .	31
8.2	The engine command . . . . .	33
8.3	The dotgen command . . . . .	34
8.3.1	dotgen genom . . . . .	34
8.3.2	dotgen template . . . . .	35
8.3.3	dotgen input . . . . .	36
8.3.4	dotgen parse . . . . .	36
8.3.5	dotgen types . . . . .	36
8.3.6	dotgen components . . . . .	37
8.4	The language command . . . . .	37
8.5	Type objects subcommands . . . . .	41
	<b>Bibliography</b>	<b>43</b>
	<b>Index</b>	<b>45</b>

# Introduction



# Component model



# **G<sup>en</sup>oM overview**



## **A minimal example**



# Input file format

This chapter describes the G<sup>en</sup>oM Input File Format (dotgen) semantics and gives the syntax for dotgen grammatical constructs.

## 5.1 Overview

The G<sup>en</sup>oM Input File Format (dotgen) is the language used to formally describe a G<sup>en</sup>oM component in terms of services and data types it provides. A description written in dotgen completely defines the interface and the internals of a component.

A description of the dotgen preprocessing is presented in section 5.2, [Preprocessing](#). The grammar is presented in section 5.3, [Dotgen grammar](#), and associated semantics is described in the rest of this chapter either in place or through references to other sub sections of this chapter.

A source file containing a dotgen component specification must have a ".gen" extension. The description of the dotgen grammar uses a syntax notation that is similar to Extended Backus-Naur Format (EBNF). Table 5.1, [dotgen EBNF symbols](#), lists the symbols used in this format and their meaning.

## 5.2 Preprocessing

A dotgen specification consists of one or more files that are preprocessed. The preprocessing performs file inclusion and macro substitution and is controlled by directives introduced by lines having # as the first character other than white space. The preprocessing is done by the C preprocessor available on the host system and configured during the build of G<sup>en</sup>oM. It is invoked as a separate process.

Symbol	Meaning
::=	Definition.
	Alternation.
text	Nonterminals.
"text"	Terminals.
( ... )	Grouping.
{ ... }	Repetition: may occur zero or any number of times.
[ ... ]	Option: may occur zero or one time.

Table 5.1: dotgen EBNF symbols

Preprocessor directives beginning with # have their own syntax (namely, the C preprocessor syntax), independent of the dotgen language and not described in this document. See for instance [1] for a documentation. Directives may appear anywhere in the source file but are not seen nor interpreted by G<sup>en</sup>oM. The primary use of the preprocessing facilities is to include definitions (especially type definitions) from other dotgen specifications. Text in files included with a #include directive is treated as if it appeared in the including file.

### 5.3 Dotgen grammar

(1)	start	::= [ spec ]
(2)	spec	::= { statement } statement
(3)	statement	::= idlstatement   genomstatement
(4)	idlstatement	::= ( module   const_dcl   type_dcl ) ";"
(5)	genomstatement	::= ( template   component   ids   attribute   port   task   service ) ";"
(6)	template	::= TEMPLATE identifier [ "{" attr_list }" ]
(7)	component	::= "component" identifier [ "{" attr_list }" ]
(8)	port	::= port_dir port_kind "<" type_spec ">" identifier port_array
(9)	port_dir	::= "inport"   "outport"
(10)	port_array	::= [ "[" "]" ]
(11)	port_kind	::= [ HANDLE ]
(12)	ids	::= scope_push_ids "{" member_list }"
(13)	attribute	::= "attribute" inited_ids_member_list
(14)	task	::= "task" identifier [ "{" attr_list }" ]
(15)	service	::= "service" identifier "(" param_list ")" [ "{" attr_list }" ]
(16)	attr_list	::= { attr ";" } attr ";"
(17)	attr	::= "doc" ":" string_literals   "version" ":" string_literals   "lang" ":" string_literals   "email" ":" string_literals   "require" ":" string_list   "codels-require" ":" string_list   "clock-rate" ":" const_expr time_unit   "period" ":" const_expr time_unit   "delay" ":" const_expr time_unit   "priority" ":" positive_int_const   "scheduling" ":" "real-time"   "stack" ":" positive_int_const size_unit   "throw" ":" event_list   "task" ":" identifier   "interrupts" ":" identifier_list   "before" ":" identifier_list   "after" ":" identifier_list   "validate" ":" validate   "codel" codel
(18)	validate	::= identifier "(" param_list ")"

(19)	code1	::= event_list ":" identifier "(" param_list ")" "yield" event_list
(20)	event_list	::= identifier_list
(21)	param_list	::= [ { param "," } param ]
(22)	param	::= ids_param_dir inited_ids_member   port_param_dir inited_port_member
(23)	inited_ids_member_list	::= { inited_ids_member "," } inited_ids_member
(24)	inited_ids_member	::= named_ids_member [ "=" initializer ]
(25)	named_ids_member	::= ids_member   ids_member ":" identifier   ":" identifier
(26)	ids_member	::= identifier   ids_member param_member
(27)	inited_port_member	::= named_port_member [ "=" initializer ]
(28)	named_port_member	::= port_member [ ":" identifier ]
(29)	port_member	::= identifier   port_member param_member
(30)	param_member	::= "." identifier   "[" positive_int_const "]"
(31)	ids_param_dir	::= "in"   "out"   "inout"
(32)	port_param_dir	::= "inport"   "outport"
(33)	initializer_list	::= [ { initializer "," } initializer ]
(34)	initializer	::= initializer_value   ":" string_literals   initializer_value ":" string_literals
(35)	initializer_value	::= const_expr   "{" initializer_list "   "[" positive_int_const "]" "=" const_expr   "[" positive_int_const "]" "=" "{" initializer_list   "." identifier "=" const_expr   "." identifier "=" "{" initializer_list "
(36)	module	::= "module" module_name "{" ( idlspec "}"   "}" )
(37)	module_name	::= identifier
(38)	idlspec	::= { idlstatement } idlstatement
(39)	const_dcl	::= "const" const_type identifier "=" const_expr
(40)	const_type	::= integer_type   char_type   boolean_type   floating_pt_type   octet_type   string_type   named_type
(41)	type_dcl	::= constructed_type   "typedef" alias_list   forward_dcl

(42)	constructed_type	::= struct_type   union_type   enum_type
(43)	alias_list	::= ( type_spec   alias_list "," ) declarator
(44)	struct_type	::= "struct" scope_push_struct "{" member_list "}"
(45)	union_type	::= "union" scope_push_union "switch" "(" switch_type_spec ")" "{" switch_body "}"
(46)	enum_type	::= "enum" identifier "{" enumerator_list "}"
(47)	forward_dcl	::= ( "struct"   "union" ) identifier
(48)	declarator	::= simple_declarator   array_declarator
(49)	simple_declarator	::= identifier
(50)	array_declarator	::= ( simple_declarator   array_declarator ) fixed_array_size
(51)	fixed_array_size	::= "[" positive_int_const "]"
(52)	type_spec	::= simple_type_spec   constructed_type_spec
(53)	simple_type_spec	::= base_type_spec   template_type_spec   named_type
(54)	constructed_type_spec	::= constructed_type
(55)	named_type	::= scoped_name
(56)	base_type_spec	::= boolean_type   integer_type   floating_pt_type   char_type   octet_type   any_type
(57)	template_type_spec	::= sequence_type   string_type   fixed_type
(58)	integer_type	::= signed_int   unsigned_int
(59)	floating_pt_type	::= float_type   double_type
(60)	signed_int	::= signed_longlong_int   signed_long_int   signed_short_int
(61)	unsigned_int	::= unsigned_longlong_int   unsigned_long_int   unsigned_short_int
(62)	unsigned_short_int	::= "unsigned" "short"
(63)	unsigned_long_int	::= "unsigned" "long"
(64)	unsigned_longlong_int	::= "unsigned" "long" "long"
(65)	signed_short_int	::= "short"
(66)	signed_long_int	::= "long"
(67)	signed_longlong_int	::= "long" "long"
(68)	float_type	::= "float"

(69)	double_type	::= "double"
(70)	char_type	::= "char"
(71)	boolean_type	::= "boolean"
(72)	octet_type	::= "octet"
(73)	any_type	::= "any"
(74)	string_type	::= "string" [ "<" positive_int_const ">" ]
(75)	sequence_type	::= "sequence" "<" simple_type_spec ( ",", positive_int_const ">"   ">" )
(76)	fixed_type	::= "fixed" [ "<" positive_int_const ",", positive_int_const ">" ]
(77)	switch_type_spec	::= integer_type   char_type   boolean_type   enum_type   named_type
(78)	switch_body	::= { case } case
(79)	member_list	::= { member ";" } member ";"
(80)	member	::= ( type_spec   member "," ) declarator
(81)	case	::= case_label_list type_spec declarator ";"
(82)	case_label_list	::= { case_label } case_label
(83)	case_label	::= ( "case" const_expr   "default" ) ":"
(84)	enumerator_list	::= { enumerator "," } enumerator
(85)	enumerator	::= identifier
(86)	scope_push_struct	::= identifier
(87)	scope_push_union	::= identifier
(88)	scope_push_ids	::= "ids"
(89)	scoped_name	::= [ [ scoped_name ] ":" ] identifier
(90)	const_expr	::= or_expr
(91)	positive_int_const	::= const_expr
(92)	or_expr	::= { xor_expr " " } xor_expr
(93)	xor_expr	::= { and_expr "^" } and_expr
(94)	and_expr	::= { shift_expr "&" } shift_expr
(95)	shift_expr	::= { add_expr ( ">>"   "<<" ) } add_expr
(96)	add_expr	::= { mult_expr ( "+"   "-" ) } mult_expr
(97)	mult_expr	::= { unary_expr ( "*"   "/"   "%" ) } unary_expr
(98)	unary_expr	::= [ "-"   "+"   "~" ] primary_expr
(99)	primary_expr	::= literal   "(" const_expr ")"   named_type
(100)	literal	::= "TRUE"   "FALSE"   integer_literal   "<float_literal>"   "<fixed_literal>"   "<char_literal>"   string_literals
(101)	string_literals	::= { string_literal } string_literal

```

(102) string_list      ::= { string_literals "," } string_literals
(103) time_unit       ::= [ "s" | "ms" | "us" ]
(104) size_unit       ::= [ "k" | "m" ]
(105) identifier      ::= "[A-Za-z_][A-Za-z0-9_]*"
                        | "s"
                        | "ms"
                        | "us"
                        | "k"
                        | "m"
                        | "real-time"
                        | TEMPLATE
                        | "component"
                        | "ids"
                        | "attribute"
                        | "version"
                        | "lang"
                        | "email"
                        | "require"
                        | "codels-require"
                        | "clock-rate"
                        | "task"
                        | "period"
                        | "delay"
                        | "priority"
                        | "scheduling"
                        | "stack"
                        | "codel"
                        | "validate"
                        | "yield"
                        | "throw"
                        | "doc"
                        | "interrupts"
                        | "before"
                        | "after"
                        | "data"
                        | HANDLE
                        | "inport"
                        | "outport"
                        | "in"
                        | "out"
                        | "inout"
(106) identifier_list ::= { identifier "," } identifier

```

## 5.4 Dotgen specification

A dotgen specification consists of one or more statements. Statements are either IDL statements, G<sup>en</sup>oM statements or cpp line directives. The syntax is:

```

(2)  spec              ::= { statement } statement
(3)  statement         ::= idlstatement
                        | genomstatement
(4)  idlstatement      ::= ( module | const_dcl | type_dcl ) ";"
(5)  genomstatement  ::= ( template | component | ids | attribute | port |
                        task | service ) ";"

```

Definitions are named by the means of identifiers: see section 5.5, **Identifiers and reserved keywords**. Cpp line directives are normally issued by the C preprocessor and are used to define the current input file name and line number (section 5.6, **Line directives**).

An IDL statement defines types (see section 5.8, **Type declaration**), constants (see section 5.9, **Constant declaration**) or IDL modules containing types and constants (see section 5.7, **Module declaration**). The syntax follows closely the subset of the OMG IDL specification corresponding to type and constants definitions (see Part I, chapter 7 of [2]). Note that this subset of the dogten grammar is not in any manner tied to OMG IDL and may diverge from future OMG specifications.

A G<sup>en</sup>oM statement defines components, communication ports, services and execution contexts called tasks.

## 5.5 Identifiers and reserved keywords

An identifier is a sequence of ASCII alphabetic, digit, and underscore (" \_") characters. The first character must be an ASCII alphabetic character.

```
(105)  identifier          ::= "[A-Za-z_][A-Za-z0-9_]*"
      | "s"
      | "ms"
      | "us"
      | "k"
      | "m"
      | "real-time"
      | TEMPLATE
      | "component"
      | "ids"
      | "attribute"
      | "version"
      | "lang"
      | "email"
      | "require"
      | "codels-require"
      | "clock-rate"
      | "task"
      | "period"
      | "delay"
      | "priority"
      | "scheduling"
      | "stack"
      | "codel"
      | "validate"
      | "yield"
      | "throw"
      | "doc"
      | "interrupts"
      | "before"
      | "after"
      | "data"
      | HANDLE
      | "inport"
      | "outport"
      | "in"
      | "out"
```

```
| "inout"
```

Words that are reserved keywords in the dotgen language are valid identifiers where their use is not ambiguous.

## 5.6 Line directives

Line directives are normally not used. They are inserted by `cpp`, as a result of preprocessing the input file (section 5.2). They can be used mostly to achieve special effects on error reporting or similar.

A line directive starts with the `#` sign, followed by the current line number and file name of the source file, optionally followed by a numeric flag. The flag is never used by G<sup>en</sup>oM. Its meaning depends on the C preprocessor used: see for instance chapter 1.8, C preprocessor output, of the FSF C preprocessor [1].

The file name and line number replace the current value kept internally by G<sup>en</sup>oM and are used in error reporting messages as well as a few other places.

## 5.7 Module declaration

A module definition satisfies the following syntax:

```
(36)  module           ::= "module" module_name "{" ( idlspec "}" | "}" )
(37)  module_name     ::= identifier
(38)  idlspec         ::= { idlstatement } idlstatement
```

The only effect of a module is to scope IDL identifiers. It is similar to a C++ or Java namespace; it is considered good practice to enclose your type definitions inside a module definition to prevent name clashes between components.

## 5.8 Type declaration

Type declarations define new data types and associate a name (an identifier) with it. The `typedef` keyword can be used to name an existing type. The constructed types `struct`, `union` and `enum` also name the type they define. The syntax is the following:

```
(41)  type_dcl        ::= constructed_type
                               | "typedef" alias_list
                               | forward_dcl
(42)  constructed_type ::= struct_type
                               | union_type
                               | enum_type
(43)  alias_list      ::= ( type_spec | alias_list "," ) declarator
```

A type specification is the description of a type. It can be used in a `typedef` construct or anywhere a typed value is expected.

```
(52)  type_spec       ::= simple_type_spec
                               | constructed_type_spec
(53)  simple_type_spec ::= base_type_spec
                               | template_type_spec
                               | named_type
```

- (56) `base_type_spec` ::= `boolean_type`  
| `integer_type`  
| `floating_pt_type`  
| `char_type`  
| `octet_type`  
| `any_type`
- (57) `template_type_spec` ::= `sequence_type`  
| `string_type`  
| `fixed_type`
- (54) `constructed_type_spec` ::= `constructed_type`
- (55) `named_type` ::= `scoped_name`
- (89) `scoped_name` ::= [ [ `scoped_name` ] ":@" ] `identifier`
- (48) `declarator` ::= `simple_declarator`  
| `array_declarator`
- (49) `simple_declarator` ::= `identifier`

## 5.9 Constant declaration

- (39) `const_dcl` ::= `"const"` `const_type` `identifier` `"="` `const_expr`



# GenoM IDL mappings

GenoM IDL is independent of the programming language used to implement the services and internals of a component. In order to use the GenoM generated source code, it is necessary for programmers to know how to access the service parameters and ports from their programming languages. This chapter defines the mapping of GenoM IDL constructs to the supported programming languages.

The mapping between GenoM IDL and a programming language diverges from the OMG CORBA standard. This is unfortunate, because this might lead to some confusion for the developers used to OMG CORBA, but it was necessary to define mappings well targetting real-time platforms. The design strategy that guided the definition of those mappings was to try to have contiguous memory segments, that do not require memory management primitives, for most of the data types. Only unbounded string and sequences do not follow this scheme.

GenoM currently implements mappings for the C and C++ languages. For the C language, see section 6.1, [C mappings](#). For the C++ language, see section 6.2, [C++ mappings](#),

## 6.1 C mappings

### 6.1.1 Scoped names

The C mappings always use the global name for a type or a constant. The C global name corresponding to a GenoM IDL global name is derived by converting occurrences of ":" to "\_" (an underscore) and eliminating the leading underscore.

### 6.1.2 Mapping for constants

In C, constants defined in dotgen are `#defined`. For instance, the following IDL:

```
const long longint = 1;
const string str = "string example";
```

would map into

```
#define longint 1
#define str "string example"
```

The identifier can be referenced at any point in the user's code where a literal of that type is legal.

IDL	C
boolean	bool
unsigned short	uint16_t
short	int16_t
unsigned long	uint32_t
long	int32_t
unsigned long long	uint64_t
long long	int64_t
float	float
double	double
char	char
octet	uint8_t
any	type any not implemented yet

Table 6.1: Basic data types C mappings

### 6.1.3 Mapping for basic data types

The basic data types have the mappings shown in Table 6.1, [Basic data types C mappings](#). Integer types use the C99 fixed size integer types as provided by the `stdint.h` standard header. Users do not have to include this header: the template mapping generation procedure output the appropriate `#include` directive along with the mappings for the integer types.

### 6.1.4 Mapping for enumerated types

The C mapping of an IDL `enum` type is an unsigned, 32 bits wide integer. Each enumerator in an `enum` is `#defined` with an appropriate unsigned integer value conforming to the ordering constraints.

For instance, the following IDL:

```
enum e {
    value1,
    value2
};
```

would map, according to the scoped names rules, into

```
typedef uint32_t e
#define e_value1 1
#define e_value2 2
```

### 6.1.5 Mapping for strings

*G<sup>en</sup>oM* IDL bounded strings are mapped to nul terminated character arrays (i.e., C strings). Unbounded strings are mapped to a pointer on such a character array.

For instance, the following *OMG* IDL declarations:

```
typedef string unbounded;
typedef string<16> bounded;
```

would map into

```
typedef char *unbounded;
typedef char bounded[16];
```

### 6.1.6 Mapping for arrays

GenoM IDL arrays map directly to C arrays. All array indices run from 0 to `size-1`.

For instance, the following IDL:

```
typedef long array[4][16];
```

would map into

```
typedef int32_t array[4][16];
```

### 6.1.7 Mapping for structure types

GenoM IDL structures map directly onto C structs. Note that these structures may potentially include padding.

For instance, the following IDL:

```
struct s {
    long a;
    long b;
};
```

would map into

```
typedef struct {
    int32_t a;
    int32_t b;
} s;
```

### 6.1.8 Mapping for union types

GenoM IDL unions map onto C structs. The discriminator in the enum is referred to as `_d`, the union itself is referred to as `_u`.

For instance, the following IDL:

```
union u switch(long) {
    case 1: long a;
    case 2: float b;
    default: char c;
};
```

would map into

```
typedef struct {
    int32_t _d;
    union {
        int32_t a;
```

```

        float b;
        char c;
    } _u;
} u;

```

### 6.1.9 Mapping for sequence types

*G<sup>en</sup>oM* IDL sequences mapping differ slightly for bounded or unbounded variations of the sequence. Both types maps onto a C struct, with a `_maximum`, `_length` and `_buffer` members.

For unbounded sequences, `buffer` points to a buffer of at most `_maximum` elements and containing `_length` valid elements. An additional member `_release` is a function pointer that can be used to release the storage associated to the `_buffer` and reallocate it. It is the responsibility of the user to maintain the consistency between those members.

For bounded sequences, `buffer` is an array of at most `_maximum` elements and containing `_length` valid elements. Since `_buffer` is an array, no memory management is necessary for this data type.

For instance, the following IDL:

```

typedef sequence<long> unbounded;
typedef sequence<long,16> bounded;

```

would map into

```

typedef struct {
    uint32_t _maximum, _length;
    int32_t *_buffer;
    void (*release)(void *_buffer);
} unbounded;

typedef struct {
    const uint32_t _maximum;
    uint32_t _length;
    int32_t _buffer[16];
} bounded;

```

## 6.2 C++ mappings

### 6.2.1 Scoped names

The C++ mappings for scoped names use C++ scopes. IDL modules are mapped to namespaces. For instance, the following IDL:

```

module m {
    const string str = "scoped string";
};

```

would map into

```

namespace m {
    const std::string str = "scoped string";
}

```

IDL	C++
boolean	bool
unsigned short	uint16_t
short	int16_t
unsigned long	uint32_t
long	int32_t
unsigned long long	uint64_t
long long	int64_t
float	float
double	double
char	char
octet	uint8_t
any	type any not implemented yet

Table 6.2: Basic data types C++ mappings

### 6.2.2 Mapping for constants

GenoM IDL constants are mapped to a C++ constant. For instance, the following IDL:

```
const long longint = 1;
const string str = "string example";
```

would map into

```
const int32_t longint = 1;
const std::string str = "string example";
```

### 6.2.3 Mapping for basic data types

The basic data types have the mappings shown in Table 6.2, [Basic data types C++ mappings](#). Integer types use the C99 fixed size integer types as provided by the `stdint.h` standard header (since the C++ `cstdint` header is not part of the C++ at the time of writing this document). Users do not have to include this header: the template mapping generation procedure output the appropriate `#include` directive along with the mappings for the integer types.

### 6.2.4 Mapping for enumerated types

The C++ mapping of an IDL `enum` type is the corresponding C++ `enum`. An additional constant is generated to guarantee that the type occupies a 32 bits wide integer.

For instance, the following IDL:

```
enum e {
    value1,
    value2
};
```

would map, according to the scoped names rules, into

```
enum e {
    value 1,
    value 2,
    _unused = 0xffffffff,
};
```

### 6.2.5 Mapping for strings

*G<sup>en</sup>oM* IDL bounded strings are mapped to nul terminated character arrays (i.e., C strings) wrapped inside the specific `genom::bounded_string` class. Unbounded strings are mapped to `std::string` provided by the C++ standard.

For instance, the following *OMG IDL* declarations:

```
typedef string unbounded;
typedef string<16> bounded;
```

would map into

```
typedef std::string unbounded;
typedef genom::bounded_string<16> bounded;
```

The `genom::bounded_string` provides the following interface:

```
namespace genom3 {
    template<std::size_t L> struct bounded_string {
        char c[L];
    };
}
```

This minimalistic definition will be refined before the official 3.0 *G<sup>en</sup>oM* release.

### 6.2.6 Mapping for arrays

*G<sup>en</sup>oM* IDL arrays map directly to C++ arrays. All array indices run from 0 to `size-1`.

For instance, the following *IDL*:

```
typedef long array[4][16];
```

would map into

```
typedef int32_t array[4][16];
```

### 6.2.7 Mapping for structure types

*G<sup>en</sup>oM* IDL structures map directly onto C++ `structs`. Note that these structures may potentially include padding.

For instance, the following *IDL*:

```
struct s {
    long a;
    long b;
};
```

would map into

```
struct s {
    int32_t a;
    int32_t b;
};
```

### 6.2.8 Mapping for union types

GenoM IDL unions map onto C structs. The discriminator in the enum is referred to as `_d`, the union itself is referred to as `_u`.

For instance, the following IDL:

```
union u switch(long) {
    case 1: long a;
    case 2: float b;
    default: char c;
};|
```

would map into

```
struct u {
    int32_t _d;
    union {
        int32_t a;
        float b;
        char c;
    } _u;
};
```

Note that the C++ standard does not allow union members that have a non-trivial constructor. Consequently, the C++ mapping for such kind of unions is not allowed in GenoM either. This concerns `sequences` and `strings`, and structures or unions that contain such a type. You should thus avoid to define such datatypes in GenoM IDL in order to maximize the portability of your definitions.

### 6.2.9 Mapping for sequence types

GenoM IDL sequences mapping differ for bounded or unbounded variations of the sequence. The unbounded sequence maps onto a C++ `std::vector` provided by the C++ standard. The bounded sequences maps onto the specific `genom3::bounded_vector` class.

For instance, the following IDL:

```
typedef sequence<long> unbounded;
typedef sequence<long,16> bounded;
```

would map into

```
typedef std::vector<int32_t> unbounded;
typedef genom3::bounded_vector<int32_t, 16> bounded;
```

The `genom::bounded_vector` provides the following interface:

```
namespace genom3 {  
    template<typename T, std::size_t L> struct bounded_vector {  
        T e[L];  
    };  
}
```

This minimalistic definition will be refined before the official 3.0 *G<sup>en</sup>oM* release.

# Running G<sup>en</sup>oM

## 7.1 Synopsis

```
genom3 [-l] [-h] [--version]
genom3 [-I dir] [-D macro[=value]] [-E|-n] [-v] [-d] file.gen
genom3 [general options] template [template options] file.gen
```

## 7.2 Description

The G<sup>en</sup>oM program is a *source code generator* that is used to generate software components from a formal description file.

The input *file* is expected to contain the description of the services, input and output ports, data types definitions and execution contexts of a software component, written in the *dotgen* language.

The dotgen specification is first processed by a C preprocessor before it is parsed by G<sup>en</sup>oM and transformed into an abstract syntax tree. The program used as a C preprocessor can be changed with the `CPP` environment variable. G<sup>en</sup>oM accepts `-I` and `-D` options that are passed unchanged to the cpp program.

The abstract syntax tree is exported in a format suitable to a *generator engine* that is in charge of a *template* execution for actual source code generation. The generator engine provides a scripting language and a set of procedures for use by templates. The directory where source code for the generator engine is searched can be changed with the `-s` option.

Templates are a set of source files that serve as the basis for source code generation. Templates source files are interpreted by the generator engine. They can contain code written in the scripting language provided by the generator engine, that computes generated output, or regular source code that is appended directly to the generated code. Intermediate files and scripts are saved in a temporary directory before they are copied to the final destination directory. The `-T` option changes the path of the temporary directory. The `-d` option will keep all temporary files instead of deleting them once the program terminates. This is useful only for template development and debugging.

The choice of a template depends on the kind of source code that is wanted by the user. Refer to the documentation of the templates for a description on what they do. The names of the available templates can be listed with the `-l` option. The directory in which templates are looked for can be changed with the `-t` option.

The G<sup>en</sup>oM program accepts *general options* that affect the general program behaviour. G<sup>en</sup>oM can also pass *template options* to the template. These options will only affect the template behaviour.

### 7.3 General options

#### **-I *dir***

Add the directory *dir* to the list of directories to be searched for included files. The *dir* argument is passed as-is to the `cpp` program via the same `-I` option.

When `-r` option is in effect (either explicitly passed on the command line, or configured by default during the build process), an implicit `-I` directive pointing to the directory of the input file is appended to the end of the list of searched directories.

#### **-D *macro*[=*value*]**

Predefine *macro*, with definition `1` or *value* if given, in the same way as a `#define` directive would do it. This option is passed as-is to the `cpp` program.

If you are invoking `genom` from the shell, you may have to use the shell quoting character to protect shell's special characters such as spaces.

An implicit macro `__GENOM__` is always defined and contains the version of the `genom` program. This can be used to divert some lines in source files meant to be included by other tools that `genom`, and that contain syntax that `genom` does not understand.

#### **-E**

Stop after the preprocessing stage, and do not run `genom` proper. The output of `cpp` is sent to the standard output. `genom` exits with a non-zero status if there are any preprocessing errors, such as a non-existent included file.

#### **-n, --parse-only**

Stop after the input file parsing stage, and do not invoke any template. This is useful to check the syntax of the input file. Any errors or warning are reported and `genom` exits with a non-zero status if there are errors.

#### **-N, --dump**

Stop after the input file parsing stage, do not invoke any template and dump the parsed specification in `dotgen` format. This is mostly useful for debugging `genom` itself or to view the actual specification built by `genom` from a complex (set of) file(s). Any errors or warning are reported and `genom` exits with a non-zero status if there are errors.

#### **-l, --list**

Print to the standard output the list of available templates. Each line of output contains the name of a template and the `genom` engine that it uses (currently, only Tcl-based templates are supported).

By default, the standard templates directory is searched, but any `-t` option will be taken into account.

#### **-t *path*, --tmpldir=*path***

Use *path* as the directory containing templates. This can be a colon separated list of directories which are searched in order.

This option is useful only for templates not installed in the `genom` standard directories, i.e. `share/genom/<version>/templates` or `share/genom/site-templates`.

*path* is searched for files matching `dir/*/template.tcl`, where `*` is the actual template name.

**-s *dir*, --sysdir=*dir***

Use *dir* as the directory holding genom engine files. This option is useful if non-standard engines are to be used. The default value is `share/genom/<version>/engines`.

*dir* should contain directories named after the engine name.

**-T *dir*, --tmpdir=*dir***

Use *dir* as the temporary directory holding intermediate files. See also the environment variable TMPDIR.

**-r, --rename**

Some `cpp` programs cannot handle correctly files with a `.gen` extension. This option will make genom call `cpp` with an input file ending in `.c`, linked to the real input file.

**-v, --verbose**

Force genom to be more verbose while processing input files.

**-d, --debug**

Activate some debugging options. In particular, temporary files are not deleted. Useful for debugging genom itself or generator engines.

**--version**

Display the version number of the invoked GenoM.

**-h, --help**

Print usage summary and exit.

## 7.4 Template options

**-h, --help**

Templates might define their own specific options. The `-h` option is always defined, and prints a summary of supported options. See the template manual for a detailed description. Template options should be passed after the template name, and before the input file name.

## 7.5 Environment variables

**0**

Define the C preprocessor program to use. The default depends on the value configured during the genom build process, but it is most often `gcc -E -xc` on Linux systems.

The CPPprogram must recognize `-I` and `-D` arguments.

**2**

The value of `GENOM_TEMPLATE_PATH` is a colon-separated list of directories, much like `PATH`, where `GenoM` looks for templates. Setting this variable overrides the default search path, but any `-t` option takes precedence over this variable.

**0**

Path to the directory holding temporary files. Defaults to `/tmp`.



# Templates

## 8.1 The template command

```
template require file
```

Source tcl *file* and make its content available to the template files. The file name can be absolute or relative. If it is relative, it is interpreted as relative to the template directory (see `dotgen template dir`).

**Parameters:**

<i>file</i>	Tcl input file to source. Any procedure that it creates is made available to the template files.
-------------	--

```
template parse [args list] [file/string/raw file ...]
```

This is the main template function that parses a template source file and instantiate it, writing the result into the current template directory (or in a global variable). This procedure should be invoked for each source file that form a template.

When invoking `template parse`, the last two arguments are the destination file or string. A destination file is specified as `file file` (the filename is relative to the current template output directory). Alternatively, a destination string is specified as `string var`, where *var* is the name of a *global* variable in which the template engine will store the result of the source instantiation.

The output destination file or string is generated by the template from one or several input source. An input source is typically a source file, but it can also be a string or a raw (unprocessed) text. An input source file is specified with `file file`, where *file* is a file name relative to the template directory. An input source read from a string is specified as `string text`, where *text* is any string, processed by the template engine as usual. Finally, a raw, unprocessed source that is copied verbatim to the destination, is specified as `raw text`, where *text* is any string.

Additionally, each input source, defined as above, can be passed a list of optional arguments by using the special `args list` construction as the first argument of the `template parse` command. The list given after `args` can be retrieved from the template source file from the usual `argv` variable.

**Examples:**

```
template parse file mysrc file mydst
```

Will parse the input file `mysrc`, process it and save the result in `mydst`.

```
template parse args {one two} file mysrc file mydst
```

Will do the same as above, but the template code in the input file `mysrc` will have the list `{one two}` accessible via the `argv` variable.

```
template parse string "test" file mydst
```

Will process the string `"test"` and save the result in `mydst`.

#### Parameters:

<i>args</i>	This optional argument should be followed by a list of arguments to pass to the template source file. It should be the very first argument, otherwise it is ignored. Each element of the list is available from the template source file in the <code>argv</code> array.
<i>perm</i>	This optional argument may be set to specify the permissions to be set for the created file.

```
template link src dst
```

Link source file *src* to destination file *dst*. If relative, the source file *src* is interpreted as relative to the template directory and *dst* is interpreted as relative to the current output directory. Absolute file name can be given to override this behaviour.

```
template options { pattern body ... }
```

Define the list of supported options for the template. Argument is a Tcl switch-like script that must define all supported options. It consists of pairs of *pattern body*. If an option matching the *pattern* is passed to the template, the *body* script is evaluated. A special body specified as `"-"` means that the body for the next pattern will be used for this pattern.

#### Examples:

```
template options {
  -h - -help { puts "help option" }
}
```

This will make the template print the text `"help option"` whenever `-h` or `-help` option is passed to the template.

```
template arg
```

Return the next argument passed to the template, or raise an error if no argument remains.

```
template usage [string]
```

With a *string* argument, this procedure defines the template "usage" message. Unless the template redefines a `-h` option with `template options`, the default behaviour of the template is to print the content of the `template usage` string when `-h` or `-help` option is passed to the template.

`template usage`, when invoked without argument, returns the last usage message defined.

```
template message [string]
```

Print *string* so that it is visible to the end-user. The text is sent on the standard error channel unconditionally.

```
template fatal [string]
```

Print an error message and stop. In verbose mode, print the source location as reported by [info frame].

## 8.2 The engine command

```
engine mode [ [+-]modespec ... ]
```

Set miscellaneous engine operating mode. The command can be invoked without argument to retrieve the current settings for all supported modes. The command can also be invoked with one or more mode specification to set these modes (see *modespec* argument below).

The list of supported modes is the following:

- **verbose**: turns on or off the verbosity of the engine.
- **overwrite**: when turned on, newly generated files will overwrite existing files without warning. When turned off, the engine will stop with an error if a newly generated file would overwrite an existing file. **overwrite** is by default off.
- **move-if-change**: when turned on, an existing file with the same content as a newly generated file will not be modified (preserving the last modification timestamp). When off, files are systematically updated. **move-if-change** is on by default.
- **debug**: when on, this mode preserves temporary files and tcl programs generated in the temporary directory. Useful only for debugging the template.

### Example:

```
engine mode -overwrite +move-if-change
```

### Parameters:

*modespec*      A mode specification string. Supported modes are **verbose**, **overwrite**, **move-if-change** **merge-if-change** and **debug**. If *mode* string is prefixed with a dash (-), it is turned off. If mode is prefixed with a plus (+) or nothing, it is turned on.

**Returns:**

When called without arguments, the command returns the current configuration of all engine modes.

```
engine merge-tool tool
```

Change the engine merge tool. When the engine is in 'merge-if-change' mode, a merge tool is invoked with the two conflicting versions of a file. If the merge tool exits successfully, the generated file is replaced by the (manually) merged version.

**Parameters:**

*tool*                      The path to the merge tool, or builtin keywords 'interactive' or 'auto'.

```
engine chdir dir
```

Change the engine output directory. By default, files are generated in the current directory. This command can be used to generate output in any other directory.

**Parameters:**

*dir*                        The new output directory, absolute or relative to the current working directory.

```
engine pwd
```

Return the current engine output directory.

## 8.3 The dotgen command

### 8.3.1 dotgen genom

Those commands implement access to genom program parameters or general information.

```
dotgen genom program
```

Returns the absolute path to the GenoM executable currently running.

```
dotgen genom cmdline
```

Returns a string containing the options passed to the GenoM program.

```
dotgen genom version
```

Returns the full version string of the GenoM program.

```
dotgen genom debug
```

Returns a boolean indicating whether genom was invoked in debugging mode or not.

```
dotgen genom stdout [on]
```

With optional boolean argument *on*, turns on or off the standard output channel of the template engine.

Without argument, the procedure returns the current activation status of the standard output channel.

**Parameters:**

*[on]* Turn on/off standard output channel.

**Returns:**

When called without argument, returns a boolean indicating the current status (on/off) of the standard output channel.

### 8.3.2 dotgen template

Those commands return information about the template currently being parsed.

```
dotgen template name
```

Return the current template name.

```
dotgen template dir
```

Return a path to the current template directory (the directory holding the template.tcl file).

```
dotgen template sysdir
```

Return a path to the genom system directory.

```
dotgen template tmpdir
```

Return a path to the temporary directory where the template engine writes its temporary files.

### 8.3.3 dotgen input

Those commands return information about the current genom input file (.gen file).

```
dotgen input file
```

Return the full path to the current .gen file.

```
dotgen input base
```

Return the base name of the current .gen file, i.e. the file name with all directories stripped out.

```
dotgen input dir
```

Return the directory name of the current .gen file.

```
dotgen input notice
```

Return the copyright notice (as text) found in the .gen file. This notice can actually be any text and is the content of the special comment starting with the three characters `'/' '*' '/'`, near the beginning of the .gen file.

### 8.3.4 dotgen parse

```
dotgen parse file|string data
```

Parse .gen data either from a file or from a string. When parsing is successful, the corresponding objects are exported to the engine.

**Parameters:**

<i>file/string</i>	Specify if parsing from a file or from a string.
<i>data</i>	When parsing from a file, data is the file name. When parsing from a string, data is the data to be parsed.

### 8.3.5 dotgen types

This command return information about the type definitions in the .gen file.

```
dotgen types [pattern]
```

This command returns the list of type objects that are defined in the current .gen file. This list may be filtered with the optional *pattern* argument. Each element of the returned list is a type command that can be used to access detailed information about that particular type object.

**Parameters:**

*[pattern]* Filter on the type names. The filter may contain a glob-like pattern (with \* or ? wildcards). Only the types whose name match the pattern will be returned.

**Returns:**

A list of type objects.

**8.3.6 dotgen components**

This command return information about the components definitions in the .gen file.

```
dotgen components [pattern]
```

This command returns the list of components that are defined in the current .gen file (normally just one). This list may be filtered with the optional *pattern* argument. Each element of the returned list is a component command that can be used to access detailed information about each particular component object.

**Parameters:**

*[pattern]* Filter on the component name. The filter may contain a glob-like pattern (with \* or ? wildcards). Only the components whose name match the pattern will be returned.

**Returns:**

A list of component objects.

**8.4 The language command**

```
language mapping ?type?
```

Generate and return the mapping of *type* for the current language, or all types if no argument is given. The returned string is a valid source code for the language.

**Parameters:**

*type* A 'type' object.

```
language declarator type [var]
```

Return the abstract declarator for *type* or for a variable *var* of that type, in the current language.

**Parameters:**

*type* A type object.

*var* A string representing the name of a variable of type *type*.

```
language address type [var]
```

Return an expression evaluating to the address of a variable in the current language.

**Parameters:**

*type* A type object.  
*var* A string representing the name of a variable of type *type*.

```
language dereference type [var]
```

Return an expression dereferencing a pointer on a variable in the current language.

**Parameters:**

*type* A type object.  
*var* A string representing the name of a variable of type *type*.

```
language argument type kind [var]
```

Return an expression that declares a parameter *var* of type *type*, passed by value or reference according to *kind*.

**Parameters:**

*type* A type object.  
*kind* Must be "value" or "reference".  
*var* A string representing the name of a variable of type *type*.

```
language pass type kind [var]
```

Return an expression that passes *var* of type *type* as a parameter, by value or reference according to *kind*.

**Parameters:**

*type* A type object.  
*kind* Must be "value" or "reference".  
*var* A string representing the name of a variable of type *type*.

```
language member type mlist
```

Return the language construction to access a member of a *type*. *mlist* is a list interpreted as follow: if it starts with a letter, *type* should be an aggregate type (like `struct`); if it starts with a numeric digit, *type* should be an array type (like `sequence`).

**Parameters:**

<i>type</i>	A type object
<i>mlist</i>	A list of hierarchical members to access.

```
language signature codel [separator [location]]
```

Return the signature of a codel in the current language. If *separator* is given, it is a string that is inserted between the return type of the codel and the codel name (for instance, a `\n` in C so that the symbol name is guaranteed to be on the first column).

**Parameters:**

<i>codel</i>	A codel object.
<i>separator</i>	A string, inserted between the return type and the codel symbol name.
<i>location</i>	A boolean indicating whether to generate <code>#line</code> directive corresponding to the codel definition in <code>.gen</code> file.

```
language invoke codel params
```

Return a string corresponding to the invocation of a codel in the current language.

**Parameters:**

<i>codel</i>	A codel object.
<i>params</i>	The list of parameters passed to the codel. Each element of this list must be a valid string in the current language corresponding to each parameter value or reference to be passed to the codel.

```
lang language
```

Set the current language for procedures that output a language dependent string

**Parameters:**

<i>language</i>	The language name. Must be <code>c</code> or <code>c++</code> .
-----------------	---

```
cname {string|object}
```

Return the canonical name of the *string* or the G<sup>en</sup>oM *object*, according to the current language.

If a regular string is given, this procedure typically maps IDL `::` scope separator into the native symbol in the given language. If a codel object is given, this procedure returns the symbol name of the codel in the given language.

**Parameters:**

<i>string</i>	The name to convert.
<i>object</i>	A G <sup>en</sup> oM object. Only class <code>codel</code> is supported at the moment.



<i>column</i>	The desired maximum length of each line
---------------	---

## 8.5 Type objects subcommands

```
$type foreach varlist ?with prefix? body
```

Evaluate *body* for each member of *type*, with *varlist* set to the current element. The result of the command is an empty string.

*varlist* is a list of one up to three variable names. The first variable is set to the current current type element, the second variable is set to the element kind and the third variable (if present) is set to a string representing the code (in the current language) for accessing the current element. If "with *prefix*" was given, this string is prefixed with the *prefix* string, so that if *prefix* contains the top variable containing *type*, the computed expression will directly access the current element.

Exploration of the type tree is done in depth-first order. *body* shall return a list of strings (maybe empty) that are concatenated and passed to "indent" when the function returns.

Note: an endless recursion is possible if the type in question has a recursive definition (e.g. a structure contains a sequence of the same structure). This potentially endless recursion is allowed on purpose, but it is important that you handle this situation in the *body* script. A potentially endless recursion can be detected if your *body* script encounters either a **forward struct** or a **forward union**. It is up to the caller to determine what to do in this case, but this typically involves returning 'continue' at some point to skip further exploration of that branch.

### Parameters:

<i>\$type</i>	A type object.
<i>varlist</i>	<i>varlist</i> A list of variable names of 1, 2 or 3 elements. First variable is set to the current element kind, second variable is set to the current element of object while iterating and optional third element is set to the current element and the hierarchy of elements leading to the current element.
<i>prefix</i>	A string prepended to the 3rd element of <i>varlist</i> . Typically contains a reference to the variable holding <i>\$type</i> .
<i>body</i>	A script evaluated for each element of object.



# Bibliography

- [1] Free Software Foundation. The C preprocessor. <http://gcc.gnu.org/onlinedocs/cpp/>.
- [2] Object Management Group. CORBA specification, version 3.1. Part I: CORBA interfaces. <http://www.omg.org/spec/CORBA/3.1/Interfaces/PDF>.



# Index

## Symboles

--- (template command) ..... 40

## C

cname (template command) ..... 39

comment (template command) ..... 40

## D

dotgen ..... 9

    grammar ..... 10

    identifier ..... 15

    specification ..... 14

dotgen (template command) ..... 34–37

    components ..... 37

    genom ..... 34, 35

        cmdline ..... 34

        debug ..... 35

        program ..... 34

        stdout ..... 35

        version ..... 35

    input ..... 36

        base ..... 36

        dir ..... 36

        file ..... 36

        notice ..... 36

    parse ..... 36

    template ..... 35

        dir ..... 35

        name ..... 35

        sysdir ..... 35

        tmpdir ..... 35

    types ..... 36

## E

engine (template command) ..... 33, 34

    chdir ..... 34

    merge-tool ..... 34

    mode ..... 33

    pwd ..... 34

## F

fileext (template command) ..... 40

foreach (template command) ..... 41

## I

identifier ..... 15

indent (template command) ..... 40

input

    file format ..... 9

    preprocessing ..... 9

## L

lang (template command) ..... 39

language (template command) ..... 37–39

    address ..... 38

    argument ..... 38

    declarator ..... 37

    dereference ..... 38

    invoke ..... 39

    mapping ..... 37

    member ..... 38

    pass ..... 38

    signature ..... 39

## P

preprocessing ..... 9

## T

template (template command) ..... 31–33

    arg ..... 32

    fatal ..... 33

    link ..... 32

    message ..... 33

    options ..... 32

    parse ..... 31

    require ..... 31

    usage ..... 33

template command

    --- ..... 40

    cname ..... 39

    comment ..... 40

    dotgen ..... 34–37

    engine ..... 33, 34

    fileext ..... 40

    foreach ..... 41

    indent ..... 40

    lang ..... 39

    language ..... 37–39

    template ..... 31–33

    wrap ..... 40

## W

wrap (template command) ..... 40